

50
AK

- 8.

1 9. The method of claim 7, wherein displaying the hyperlink comprises
2 displaying a hyperlink associated with a uniform resource locator having a protocol
3 identifier and a string representing a logical identifier of a callee.

1 10. The method of claim 9, wherein the logical identifier comprises a
2 telephone number.

1 11. The method of claim 9, wherein the protocol identifier comprises a
2 ☒ predetermined identifier to identify the uniform resource locator as a telephony-related
3 uniform resource locator.

1 12. The method of claim 1, further comprising copying the hyperlink from a
2 first storage location accessible by a browser to a second storage location accessible by
3 another application routine.

1 13. The method of claim 1, further comprising establishing a call session with
2 a remote terminal.

1 14. A device capable of participating in call sessions over a data network,
2 comprising:
3 a display;
4 a hyperlink presentable in the display and selectable by a user; and
5 a controller to generate a call request in response to selection of the
6 hyperlink.

1 15. The device of claim 14, further comprising a storage device containing
2 call rules, the controller to access the call rules to determine how the call request is to be
3 generated.

1 16. The device of claim 15, the controller to determine if the call request is a
2 local call or a toll call based on the call rules.

007650-99725500

1 17. The device of claim 15, the controller to add one or more special
2 characters to provide a function based on the call rules.

1 18. The device of claim 17, wherein the function is selected from the group
2 consisting of disabling call waiting, inserting a pause, and navigating an automated
3 attendant.

1 19. The device of claim 15, the controller to add charge information to a call
2 request based on the call rules.

1 20. The device of claim 14, wherein the hyperlink is presentable in a browser
2 screen in the display.

1 21. The device of claim 14, wherein the hyperlink is associated with a label
2 that is presentable in the display and a uniform resource locator that is contained in the
3 call request.

1 22. The device of claim 14, wherein the hyperlink is associated with a uniform
2 resource locator containing a logical identifier of a callee, the logical identifier being
3 contained in the call request.

1 23. The device of claim 22, wherein the uniform resource locator further
2 contains a predetermined protocol identifier to identify the uniform resource locator as a
3 telephony-based uniform resource locator.

00562456 003400

- 1
- 2
- 3
- 4
- 5
- 6
- 7

- 1
- 2
- 3

1
2

1
2

- 1
- 2
- 3

- 1
- 2
- 3
- 4
- 5
- 6

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8

- 1
- 2
- 3

- 1
- 2
- 3